

## SDS Oxygen (Compressed gas)

Manufacturer/Importer/Distributor:  
INFRA S.A. DE C.V.  
Felix Guzman No.16, 3<sup>rd</sup> floor, El Parque,  
53398, Naucalpan, State of Mexico, Mexico.  
**EMERGENCY TELEPHONE NUMBER: 800-221-98-44**  
(24 h)

**Document key:**  
SDS 001 02 O<sub>2</sub>

**Review Number:** 3

**Print day:**  
2016-07-22

**Review date:** 2024-06-05  
**Next review:** 2026-06-05

Page 1 of 8

### 1.- Product and Company Identification

Product name:  
**Oxygen**

Chemical family<sup>1</sup>:  
**Oxidizing gases**

Relevant :  
**Nonflammable gas**  
**Oxidizing gas**  
**Compressed gas**

Chemical formula:  
**O<sub>2</sub>**

Product Use Description:  
Medical Applications.

### 2.- Hazards Identification

GHS classification:

Oxidizing gases - Category 1.  
Gases under pressure - Compressed gas.

GHS label elements:

Hazard pictograms/symbols



Signal Word: **"Danger"**

Hazard Statements:

**H270:** May cause or intensify fire: oxidizer.  
**H280:** Contains gas under pressure; may explode if heated.

Precautionary Statements:

**Prevention:**

**P220:** Keep away from clothing and other combustible materials.  
**P244:** Keep valves and fittings free from oil and grease.

**Response:**

**P370+P376:** In case of fire: Stop leak if safe to do so. **P314:** Get medical advice/attention if you feel unwell.

**Storage:****P410+P403:** Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise classified:

- High pressure, oxidizing gas.
- Vigorously accelerates combustion.
- Keep oil, grease, and combustibles away.
- May react violently with combustible materials.

### 3.-Composition/Information on ingredients

Concentration (volume):	No. UN:	Sinonyms:	No. CAS <sup>2</sup> :
100%	1072	Oxygen, Oxygen gas, Gaseous Oxygen, GOX	7782-44-7

Concentration is nominal. For the exact product composition, please refer to Infra technical specifications.

### 4.-First Aid Measures

General advice:	Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Eye contact:	Seek medical advice.
Skin contact:	Seek medical advice.
Ingestion:	Ingestion is not considered a potential route of exposure. Inhalation.
Inhalation:	Consult a physician after significant exposure. Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
Most important symptoms/effects - acute and delayed:	If oxygen is administered to persons with chronic obstructive pulmonary disease, raising the oxygen concentration in the blood depresses their breathing and raises their retained carbon dioxide to a dangerous level.

### 5.-Fire-Fighting Measures

Suitable extinguishing media:	All known extinguishing media can be used.
Specific hazards:	Most cylinders are designed to vent contents when exposed to elevated temperatures.
Further information	Some materials that are noncombustible in air will burn in the presence of an oxygen enriched atmosphere (greater than 23.5%). Fire resistant clothing may burn and offer no protection in oxygen rich atmospheres.

## 6.-Accidental release measures

Personal Precautions, Protective Equipment, and Emergency Procedures:	Clothing exposed to high concentrations may retain oxygen 30 minutes or longer and become a potential fire hazard. Stay away from ignition sources. Evacuate personnel to safe areas. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ventilate the area.
Environmental precautions:	Do not discharge into any place where its accumulation could be dangerous.
Methods for cleaning up:	Prevent further leakage or spillage if safe to do so. Ventilate the area.
Additional advice:	If possible, stop flow of product. Increase ventilation to the release area and monitor concentrations. If leak is from cylinder or cylinder valve, call the Infra emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.

## 7.-Handling and Storage

### Handling:

- All gauges, valves, regulators, piping and equipment to be used in oxygen service must be cleaned for oxygen service.
- Oxygen is not to be used as a substitute for compressed air.
- Never use an oxygen jet for cleaning purposes of any sort, especially clothing, as it increases the likelihood of an engulfing fire.
- Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Protect cylinders from physical damage; do not drag, roll, slide or drop.
- Do not allow storage area temperature to exceed 50°C (122°F).
- Before using the product, determine its identity by reading the label.
- Know and understand the properties and hazards of the product before use.
- When doubt exists as to the correct handling procedure for a particular gas, contact the supplier.
- Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- Use an adjustable strap wrench to remove over-tight or rusted caps.
- Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials.
- Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction.
- Ensure the complete gas system has been checked for leaks before use.
- Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container.
- Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings.
- Doing so may damage valve, causing a leak to occur. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied.

Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.

- Do not smoke while handling product or cylinders.
- Never re-compress a gas or a gas mixture without first consulting the supplier.
- Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping.
- When returning cylinder install valve outlet cap or plug leak tight.
- Never permit oil, grease, or other readily combustible substances to come into contact with valves or containers containing oxygen or other oxidants.
- Do not use rapidly opening valves (e.g. ball valves).
- Open valve slowly to avoid pressure shock. Never pressurize the entire system at once.
- Use only with equipment cleaned for oxygen service and rated for cylinder pressure.
- Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F).

#### Storage:

- Do not change or force fit connections.
- Always keep container in upright position.
- Use a back flow preventative device in the piping.
- Use only with equipment cleaned for oxygen service and rated for cylinder pressure.
- Use only with equipment of compatible materials of construction, rated for cylinder pressure.
- Open/close valve slowly.
- Close when not in use.
- Wear Safety Eye Protection.
- Check Safety Data Sheet before use.
- Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air.
- Full containers should be stored so that oldest stock is used first.
- Stored containers should be periodically checked for general condition and leakage.
- Observe all regulations and local requirements regarding storage of containers.
- Protect containers stored in the open against rusting and extremes of weather.
- Containers should not be stored in conditions likely to encourage corrosion.
- Containers should be stored in the vertical position and properly secured to prevent toppling.
- The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged.
- Container valve guards or caps should be in place.
- Keep containers tightly closed in a cool, well-ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Full and empty cylinders should be segregated.
- Do not allow storage temperature to exceed 50°C (122°F). Display "No Smoking or Open Flames" signs in the storage areas.
- Return empty containers in a timely manner.
- Flammable storage areas should be separated from oxygen and other oxidizers by a minimum distance of 20 ft. (6.1 m.) or by a barrier of non-combustible material at least 5 ft. (1.5 m.) high, having a fire resistance rating of at least 1/2 hour.

#### Technical measures/Precautions:

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) And in accordance with local regulations.

## 8.-Exposure controls/Personal protection

### Engineering measures:

Ensure adequate ventilation.

### Personal protective equipment:

#### Respiratory protection:

Users of breathing apparatus must be trained.

#### Hand protection:

Wear working gloves when handling gas containers.  
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### Eye protection:

Safety glasses recommended when handling cylinders.

#### Skin and body protection:

Safety shoes are recommended when handling cylinders.

#### Special instructions for protection and hygiene:

Ensure adequate ventilation, especially in confined areas. Gloves must be clean and free of oil and grease.

## 9.-Physical and Chemical Properties

Color and Smell:	Colorless and odorless
Physical state:	Compressed gas
Odor threshold:	NA
pH:	NA
Melting point @ 1 atm (°C):	-218.79
Boiling point @ 1 atm (°C):	-182.98
Flashpoint (°C):	NA
Evaporation rate:	NA
Flammability limits (% vol./vol. in air):	NA
Flammability limits (% vol./vol. in oxygen):	NA
Vapor pressure @ 21.1 °C ( kPa):	ND
Vapor density @ 21.1°C; 1 atm:	ND
Relative density of gas @ 21.1°C; 1 atm (aire = 1):	1.105
Gas density @ 21.1°C; 1 atm (kg/m³):	1.325
Water solubility @ 0°C (vol./vol.) :	0.0491
Partition coefficient: n-octanol/agua (logKOW):	NA
Decomposition temperature (°C):	NA
Auto ignition temperature (°C):	NA
Sublimation temperature @ 1 atm (°C):	NA

<b>Gas viscosity @ 25°C (micropoise):</b>	201.74
<b>Molecular weight (g/mol):</b>	31.99
<b>Reactivity in water:</b>	NA
<b>Volatility percentage:</b>	NA

## 10.-Stability and Reactivity

Chemical Stability:	Stable under normal conditions.
Conditions to avoid:	No data available.
Materials to avoid:	Flammable materials. Organic materials. Avoid oil, grease and all other combustible materials.
Hazardous decomposition products:	No data available.
Possibility of hazardous Reactions/Reactivity:	No data available.

## 11.-Toxicological Information

### Information on toxicological effects

#### Likely routes of exposure:

<b>Effects on Eye:</b>	No adverse effect.
<b>Effects on Skin:</b>	No adverse effect.
<b>Inhalation Effects:</b>	Breathing 75% or more oxygen at atmospheric pressure for more than a few hours may cause nasal stuffiness, cough, sore throat, chest pain and breathing difficulty. Breathing pure oxygen under pressure may cause lung damage and also central nervous system effects.
<b>Ingestion Effects:</b>	Ingestion is not considered a potential route of exposure.
<b>Symptoms:</b>	No data available.

#### Acute toxicity:

<b>Acute Oral Toxicity:</b>	No data is available on the product itself.
<b>Inhalation:</b>	No data is available on the product itself.
<b>Acute Dermal Toxicity:</b>	No data is available on the product itself.
<b>Skin corrosion/irritation:</b>	No data available.
<b>Serious eye damage/eye Irritation:</b>	No data available.
<b>Sensitization:</b>	No data available.

#### Chronic toxicity or effects from long term exposures:

<b>Carcinogenicity:</b>	No data available.
<b>Reproductive toxicity:</b>	No data is available on the product itself.
<b>Germ cell mutagenicity:</b>	No data is available on the product itself.
<b>Specific target organ systemic toxicity (single exposure):</b>	No data available.
<b>Specific target organ systemic toxicity (repeated exposure):</b>	No data available.
<b>Aspiration hazard:</b>	No data available.

## Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

If oxygen is administered to persons with chronic obstructive pulmonary disease, raising the oxygen concentration in the blood depresses their breathing and raises their retained carbon dioxide to a dangerous level.

Premature infants exposed to high oxygen concentrations may suffer delayed retinal damage that can progress to retinal detachment and blindness. Retinal damage may also occur in adults exposed to 100% oxygen for extended periods (24 to 48 h). At two or more atmospheres central nervous system (CNS) toxicity occurs. Symptoms include nausea, vomiting, dizziness or vertigo, muscle twitching, vision changes and loss of consciousness and generalized seizures. At three atmospheres, CNS toxicity occurs in less than two hours and at six atmospheres in only a few minutes.

## 12.-Ecological Information

### Ecotoxicity effects

Aquatic toxicity:	No data is available on the product itself.
Toxicity to other organisms:	No data available.

### Persistence and degradability

Biodegradability	No data is available on the product itself.
Mobility	No data available.
Bioaccumulation	No data is available on the product itself.

### Further information

This product has no known ecotoxicological effects.

## 13.-Disposal considerations

<b>Waste from residues / unused products:</b>	Return unused product in original cylinder to supplier. Contact supplier if guidance is required.
---	---

<b>Contaminated packaging:</b>	Return cylinder to supplier.
--------------------------------	------------------------------

## 14.-Transport Information

### DOT/ IATA/IMDG/TDG:

<b>UN/ID No.:</b>	UN 1072
<b>Proper shipping name:</b>	Oxygen, compressed
<b>Class or Division:</b>	2.2
<b>Label(s):</b>	2.2 (5.1)



<b>Marine Pollutant:</b>	No.
--------------------------	-----

### Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact an Infra customer service representative.

## 15.-Regulatory Information

Toxic Substance Control Act (TSCA) 12(b) Component(s): None.

Country	Regulatory	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

### EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification

Acute Health Hazard.

### US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

## 16.-Other information

### NFPA Rating

Health:	0
Fire:	0
Instability:	0
Special:	OX

### HMIS Rating

Health:	0
Flammability:	0
Physical hazard:	3
Personal Protection Equipment:	A

**Prepared by INFRA S.A. DE C.V. Industrial Safety Management.**

This Safety Data Sheet has been established in accordance with the applicable Mexican regulations (NOM-018-STPS-2015).

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.